



AUTOMOTIVE CORPORATION

STEERABLE DRIVE AXLE SPECIFICATIONS FABCO MODEL SDA-1800

The Fabco Model SDA-1800 Steerable Drive Axle is an exposed Cardan joint design, intended for use on-highway with rough terrain capability.

Maximum Capacity	18,000 Pounds Load Rating
Brakes	
Type	Drum, S-cam
Size	16.5 Diameter x 6 Inch
Chamber	30 Square Inch
Certification	FMVSS 121
Slack Adjusters	Automatic
Housing	Fabricated Steel, Cast Banjo, Center Bowl
Camber	1/2 Degrees Positive
Wheels	
Mounting	10-Studs on 11.25 Inch Bolt Circle
Minimum Wheel Size	20 Inch
Differential Carrier	Spiral Bevel
Ring Gear Diameter	16.5 Inch
Pinion Spline	2.00 Inch Diameter, 39 Spline Involute
Single Reduction Ratios	3.90, 4.11, 4.33, 4.56, 4.88, 5.29, 5.57, 6.17, 6.57, 7.17
Universal Joint	Single Cardan, 9C
Steering	Ackerman to Match Wheelbases 160" to 185" or 186" to 219" Dual Steering Arms
Kingpins	
Type	Spherical, Nylatron Races
Inclination	5 Degrees
Track	91.95 Inches across Wheel Mounting Faces
Axle Shafts	
Spline	2.100 Inch Diameter, 41 Spline Involute
Body	1.95 Inch Diameter
Turn Angle	35 Degrees
Lubrication	
Type	SAE 90, 140, 80W-140
Capacity	15 Quarts (Est.)
Weight – Dry	1,550 Lb.

OPTIONS: 10-Studs on 13 3/16 Inch, 285.75mm or 335mm B.C.
Double Reduction Ratios: 5.31, 5.61, 5.91, 6.21, 6.65, 7.21, 7.60, 8.38, 8.96, 9.77
axle tracks

For parts or service call us
Pro Gear & Transmission, Inc.



1 (877) 776-4600

(407) 872-1901

parts@eprogear.com

906 W. Gore St.

Orlando, FL 32805



